SAUDI ARABIAN OIL COMPANY (Saudi Aramco)

GENERAL INSTRUCTION MANUAL

ISSUING ORG. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT

SUBJECT RIGGING HARDWARE REQUIREMENTS

G. I. Number	Approved
7.0	29
ISSUE DATE	REPLACES
07/03/2011	07/14/2007
APPROVAL	PAGE NO.
AFW	1 of 8

1.0 **PURPOSE**

This General Instruction (GI):

- Defines the requirements for carrying out the inspections, testing, and recordkeeping of slings and other commonly used rigging hardware; and
- 1.2 Improves Saudi Aramco and contractor safety performance when using slings and other rigging hardware.

REFERENCES 2.0

It shall be the responsibility of Saudi Aramco USERS and contractors to be familiar with the current version of the publications referenced below.

ASME: American Society of Mechanical Engineers SAES: Saudi Aramco Engineering Standard

A) ASME B18.15 Forged Eyebolts

B) ASME B30.9 Slings C) ASME B30.10 Hooks

D) ASME B30.20 Below-the-Hook Lifting Devices

E) GI 7.030 Inspection and Testing Requirements for Elevating/Lifting Equipment

F) IPT's Crane and Rigging Handbook

W.G. (Bill) Newberry's Handbook for Riggers G)

H) Wire Rope Technical Board Wire Rope Users Manual

3.0 **SCOPE**

This GI covers all rigging hardware used within Saudi Aramco facilities, on Saudi Aramco jobsites outside of operating facilities, off Saudi Aramco property under a Saudi Aramco contract, and in applicable Saudi Aramco domestic joint venture companies.

DEFINITIONS 4.0

- 4.1 CERTIFIED INSPECTOR - A person certified by the Saudi Aramco Inspection Department to perform inspections and certifications on elevating/lifting equipment (For additional information, refer to Inspection Department definition in GI 7.030).
- 4.2 D/d RATIO - The mathematical formula used to determine the rated load of each side of a sling bent over a support (shackle pin, hook, etc.). The D/d Ratio is calculated by dividing the diameter of curvature around which the body of the sling is bent (D) by the diameter of the sling (d).
- 4.3 RIGGING HARDWARE - The items used to rig, lift, secure, and/or support a load. Examples include, but are not limited to, slings, shackles, eyebolts, master links, etc.
- 4.4 SAFE WORKING LOAD (SWL) - The maximum load which can be applied under general conditions of use to a crane, hoist, rope, chain, sling, or other rigging hardware. The component with the lowest SWL limits the system Safe Working Load capacity. SWL is also called Work Load Limit (WLL) or Recommended Working Load (RWL).

* CHANGE	** ADDITION	NEW INSTRUCTION \square	COMPLETE REVISION□

SAUDI ARABIAN OIL COMPANY (Saudi Aramco) G. I. Number Approved **GENERAL INSTRUCTION MANUAL** 7.029 **ISSUE DATE REPLACES** ISSUING ORG. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT 07/03/2011 07/14/2007 **APPROVAL** PAGE NO. **SUBJECT** RIGGING HARDWARE REQUIREMENTS **AFW** 2 of 8 4.5 USER - The Saudi Aramco proponent department or other organization authorized to act on behalf of the Saudi Aramco proponent department. 5.0 **GENERAL** 5.1 All sling types shall have identification information permanently affixed with durable identification tags or wire rope swages (See Section 6 for specific sling type identification tag requirements) and shall be maintained by the USER so as to be legible during the life of the sling. 5.2 Sling proof-load test certificates shall be properly filed by the USER. 5.3 Slings shall be shortened, or otherwise adjusted, only by methods approved by the sling manufacturer. 5.4 Slings shall not be shortened or lengthened by knotting, by re-splicing, or by wire rope clips. 5.5 Use of slings that have been repaired shall be prohibited. 5.6 Slings shall be hitched in a manner that provides the best control of the load. 5.7 Slings or other rigging hardware in contact with sharp corners shall be padded with material of sufficient strength to minimize damage to the sling, other rigging hardware, and/or the load being lifted. 5.8 Working conditions that may affect slings and other rigging hardware shall be considered, with special attention to temperatures, chemicals, abrasions, etc. 5.9 The rigging hardware manufacturer's rated SWL capacity shall not be exceeded. 5.10 When not in immediate use, slings and other rigging hardware shall be stored in an area where they will not be subjected to mechanical damage, corrosive action, direct sunlight, abrasives, moisture, extreme heat, and/or kinking. 5.11 All attaching devices (i.e., rings, links, coupling pins, etc.) shall be selected to provide capacities equal to, or greater than, the slings used. 5.12 Fasteners manufactured in-house from bolts, rods, pins, hooks, etc. shall not be used. 5.13 Approved, self-closing safety latches shall be used on all hooks designed for safety latches. 5.14 Horizontal sling angles less than thirty degrees (30°) shall not be used. 5.15 The USER may request that a certified inspector (See Paragraph 4.1; also refer to GI 7.030) perform assessments of slings and other rigging hardware. Such assessments shall be in accordance with ASME B30.9, B30.20, and this GI. It is recommended that the USER perform assessments of slings and other rigging hardware during their regular safety inspections. NOTE: Only technical clarification on issues related to slings and rigging hardware shall be provided by T&ESD. 5.16 Defective or damaged rigging hardware, or rigging hardware that does not comply with Saudi Aramco requirements, shall be immediately removed from service and shall be destroyed to prevent further use. Slings

CHANGE ** ADDITION NEW INSTRUCTION ☐ COMPLETE REVISION☐

removed from service shall be recorded in the sling inspection log maintained by the USER.

			OMPANY (Saudi Aramco)	G. I. Number	Approved
GEN	ERAL	INST	RUCTION MANUAL		029
ISSUIN	SSUING ORG. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT		1SSUE DATE 07/03/2011	REPLACES 07/14/2007	
SUBJEC	СТ	RIGG	ING HARDWARE REQUIREMENTS	APPROVAL AFW	PAGE NO. 3 of 8
	5.17	Alloy steel chain slings shall not be used in temperatures greater than 316 degrees C (600 degrees F) or le than -40 degrees C (-40 degrees F).			
	5.18	Alloy steel chain sling links shall be measured by the USER prior to use to verify that they have not stretched beyond the manufacturer's acceptable limits.			ot stretched
	5.19	Eyes in	Eyes in wire rope slings shall not be formed using knots.		
	5.20		the D/d ratio for using wire rope slings is less than 25, the rated load (or sed accordingly. Consult the sling manufacturer for specific data or refer to l.		
	5.21	All wir	e rope slings shall be the Flemish eye type with swaged endings. Fold backted.	c eyes for wire ro	ope slings is
	5.22	Alumir	num is prohibited as a material for use as wire rope sling ferrules.		
6.0.	PURCI	HASING	SLINGS		
	6.1	Slings	- General		
		The US	SER purchasing department shall verify that:		
		6.1.1	All purchased slings conform to ASME B30.9 as a minimum.		
		Natural and synthetic fiber rope slings have been tested to a minimum design safety factor in accordance with ASME B30.9.			y factor in
		6.1.3	All other slings meet the minimum design safety factor of 5:1.		
		6.1.4 <u>All</u> slings have been proof-tested by the manufacturer at 200% of the rated capacity. The USER shall provide, upon request, a copy of the proof-load test certificate. Proof-load test certificates for slings purchased by contractors shall be maintained by the contractor and be available for review by Saudi Aramco representatives upon request.			es for slings
		6.1.5	Unique slings required for heavy lift rigging or other special applications standard as a minimum. In cases where the load charts of ASME B30.1 type, or size of the sling to be used, the manufacturer's recommendations slipe.	9 do not cover tl	
	6.2	Alloy S	Steel Chain Slings		
		6.2.1	Alloy steel chain sling identification tags shall state: a. Manufacturer b. Grade of steel c. Reach d. Number of legs e. SWL and angle upon which the rating is based f. Identification number (ID #) which links to the certificate of proof	f-load test.	
	6.3	Metal l	Mesh Slings		
		6.3.1	Metal mesh sling identification tags shall state: a. Manufacturer		

NEW INSTRUCTION ☐ COMPLETE REVISION☐

* CHANGE

** ADDITION

SAUDI ARABIAN OIL COMPANY (Saudi Aramco) G. I. Number Approved **GENERAL INSTRUCTION MANUAL** 7.029 **ISSUE DATE** REPLACES ISSUING ORG. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT 07/03/2011 07/14/2007 **APPROVAL** PAGE NO. **SUBJECT** RIGGING HARDWARE REQUIREMENTS **AFW** 4 of 8 b. SWL rating for a basket hitch SWL rating for a choker hitch c. d. Identification number (ID #) which links to the certificate of proof-load test. 6.4 Natural and Synthetic Fiber Rope Slings 6.4.1 Natural and synthetic fiber rope sling identification tags shall state: Manufacturer a. Date of manufacture b. c. Type of material used Manufacturer's code or stock number d. SWL ratings for approved hitches used e. f. Identification number (ID #) which links to the certificate of proof-load test.

6.5 Synthetic Webbed Slings

6.4.2

- 6.5.1 Stitching shall be the only method used to fabricate synthetic webbed slings.
- 6.5.2 Synthetic webbed slings identification tags shall state:

Coated slings shall be proof-load tested before coating.

- a. Manufacturer
- b. Date of manufacture
- c. Type of material used
- d. Manufacturer's code or stock number
- e. SWL ratings for approved hitches used
- f. Identification number (ID #) which links to the certificate of proof-load test.

6.6 Wire Rope Slings

- 6.6.1 Wire rope sling identification tags shall state:
 - a. Manufacturer
 - b. SWL rating
 - c. Identification number (ID #) which links to certificate of proof-load test.

7.0 RIGGING HARDWARE

- 7.1 All rigging hardware shall meet the minimum design safety factor of 5:1.
- 7.2 Hooks, rings, oblong links, pear-shaped links, welded or mechanical coupling links, or other attachments shall have a rated load capacity equal to, or greater than, that of the alloy steel chain with which they are used.
- *7.3 All rigging hardware shall have been proof load tested by the manufacturer at 200% of the rated capacity. All rigging hardware certificates shall show individual rigging hardware serial numbers, a minimum 5:1 design safety factor, and a minimum of 200% proof load test.
- 7.4 The general construction, required information markings, inspection requirements, testing, maintenance, and utilization of rigging hardware shall be as specified in ASME B30.20 and this GI.

8.0 INSPECTION

8.1 Inspection of slings and rigging hardware shall be of two (2) types:

* CHANGE ** ADDITION NEW INSTRUCTION ☐ COMPLETE REVISION☐

SAUDI ARABIAN OIL COMPANY (Saudi Aramco) GENERAL INSTRUCTION MANUAL		G. I. Number Approved 7.029		
ISSUING ORG.	G. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT		ISSUE DATE 07/03/2011	REPLACES 07/14/2007
SUBJECT	RIGGI	NG HARDWARE REQUIREMENTS	APPROVAL AFW	PAGE NO. 5 of 8
	8.1.1	<u>Frequent inspection</u> - Visual examination by a Saudi Aramco certified use. Records are not required.	rigger (See GI 7.0	28) prior to
	8.1.2	<u>Periodic inspection</u> - Detailed visual inspection by a Saudi Aramco cer a maximum of six (6) month intervals. The inspection is recorded in 9657) [See Attachment #1], listing any deficiencies found. Record USER.	the Sling Inspection	on Log (SA
8.2	All rigg	ing hardware shall be inspected in accordance with ASME B30.20 standard	ds and this GI.	
8.3		e inspection records (See Paragraph 8.1.2) shall be kept for the life of the following information:	the sling and, as a	minimum,
	8.3.1	Frequency of sling use		
	8.3.2	Severity of service conditions		
	8.3.3	Nature of lifts being made		
	8.3.4	Experience gained on the service life of slings used in similar circumsta	ances.	
8.4	All freq	uent and periodic sling inspections shall be performed by a Saudi Aramco	certified rigger.	
8.5	as a mir	gs, upon arrival from the manufacturer, shall be inspected by the USER a nimum, entered into the Sling Inspection Log. Additional information shall be and during all periodic inspections. Each sling shall have its own Sling	nall also be logged	in prior to
	8.5.1	Serial number (ID #)		
	9.5.2	Sling type		
	8.5.3	Sling description (including length and width or diameter)		
	8.5.4	Safe working load (SWL)		
	8.5.5	In-service date		
	8.5.6	Out-of-service date		
	8.5.7	Rigger name and Saudi Aramco rigger certificate number/rigging combadge #	mpetent person Sau	ıdi Aramco
	8.5.8	Inspection date		
	9.5.9	Remarks (results of inspection).		
8.6	Sling insp	ection logs and rigging hardware shall be assessment items in safety inspec	ctions conducted by	y USERs.
	Rigging hardware that does not comply with Saudi Aramco requirements shall be immediately removed from service and shall be destroyed to prevent further use.			

NEW INSTRUCTION \square

COMPLETE REVISION□

* CHANGE

** ADDITION

	BIAN OIL COMPANY (Saudi Aramco)		G. I. Number	Approved
	GENERAL INSTRUCTION MANUAL		7.029 ISSUE DATE REPLACES	
ISSUING OF		MENT SERVICES DEPARTMENT	07/03/2011 APPROVAL	07/14/2007 PAGE NO.
SUBJECT	RIGGING HARDWARE REQUI	REMENTS	AFW	6 of 8
9.0 AT	TACHMENTS			
9.1	Attachment #1 – Sling Inspection Log (SA 9657)		
		,		
* CHANGE	** ADDITION	NEW INSTRUCTION ☐ CO	OMPLETE REVI	SION□

SAUDI ARABIAN GENERAL	G. I. Number Approved 7.029			
GENERAL INSTRUCTION MANUAL ISSUING ORG. *TRANSPORTATION & EQUIPMENT SERVICES DEPARTMENT			ISSUE DATE 07/03/2011	REPLACES 07/14/2007
SUBJECT	RIGGING HARDWARE REQUIREMENTS		APPROVAL AFW	PAGE NO. 7 of 8
Recommend	ed by: Manager Transportation & Equipment Services D	epartment		7 61 6
Concurred b	Manager Inspection Department			
Concurred b	Manager Loss Prevention Department			
Concurred b	Executive Director Industrial Services			
Approved by	Senior Vice President Operations Services			
* CHANGE	** ADDITION NEW INSTRU	JCTION □ CO	OMPLETE REVI	SION□

SLING INSPECTION LOG* *NOTE: EACH SLING SHALL HAVE A SEPARATE SLING INSPECTION LOG PAGE					
SLING TYPE:		SLING SERIAL #:	SAFE WORKING LOAD (SWL):		
SLING DESC	ERIPTION:				
SLING IN-SE	ERVICE DATE:	SLING OUT-OF-SERVICE DATE:	<u> </u>		
INSPECTION DATE	RIGGER NAME, CERTIFIC	CATE #, & SAUDI ARAMCO ID #	REMARKS		